
SAFETY DATA SHEET

SECTION 1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Product Name: SHIFT
TAR & GLUE REMOVER
- Product Part Number: 3900500xx

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Use of the substance/mixture: Automotive care, Surface treatment

1.3 Details of the supplier of the safety data sheet

- Name of Supplier: Iain Semple Chemicals Limited
- Address of Supplier: 7 McKenzie Street
Paisley
Renfrewshire
PA3 1LX
- Telephone: 0141 848 7557
- Responsible Person: Iain Semple
- Email: Info@iainsemplechemicals.co.uk

1.4 Emergency telephone number

- Emergency Telephone: 0141 848 7557

SECTION 2 Hazards identification

2.1 Classification of the substance or mixture

- CLP: Asp. Tox. 1, Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2, STOT RE 1, Aquatic Chronic

2.2 Label elements



- Signal Word: Danger
- Hazard statements
 - H226 - Flammable liquid and vapour.
 - H372 - Causes damage to organs through prolonged or repeated exposure.
 - H315 - Causes skin irritation.
 - H319 - Causes serious eye irritation.
 - H304 - May be fatal if swallowed and enters airways.
 - H411 - Toxic to aquatic life with long lasting effects.
 - EUH066 - Repeated exposure may cause skin dryness or cracking.
- Precautionary statements
 - P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 - P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

SECTION 2 Hazards identification (....)

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 - Do NOT induce vomiting.

2.3 Other hazards

SECTION 3 Composition/information on ingredients

3.1 Mixtures

- xylene
CAS Number: 1330-20-7
EC Number: 215-535-7
Concentration: 29.83%
Categories: Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2
 - Hydrocarbons, C9-12, n-alkanes, isoalkanes, Cyclics, Aromatics (2-25%)
CAS Number: 64742-88-7
EC Number: 919-446-0
Concentration: 60%
Categories: STOT SE 3, STOT RE 1, Aquatic Chronic 2
 - 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve
CAS Number: 111-76-2
EC Number: 203-905-0
Concentration: 8.64%
Categories: Skin Irrit. 2, Eye Irrit. 2
 - Oleylamine Ethoxylate
CAS Number: 26635-93-8
EC Number: 500-048-7
Concentration: 0.66%
Categories: Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1
 - Coco Alkylamine Ethoxylate
CAS Number: 61791-14-8
EC Number: 500-152-2
Concentration: 0.75%
Categories: Eye Irrit. 2
-

SECTION 4 First aid measures

4.1 Description of first aid measures

- P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P332+P313 - If skin irritation occurs: Get medical advice/attention.
- P362 - Take off contaminated clothing.

SECTION 4 First aid measures (....)

- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331 - Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Mildly irritating to respiratory system
- In cases of severe exposure, dizziness, confusion, headache or stupor may develop

- Mildly irritating to skin and eyes
- Can cause damage to the eyes, skin and mucous membranes

4.3 Indication of any immediate medical attention and special treatment needed

- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 - P101 - If medical advice is needed, have product container or label at hand.
 - If substance has got into eyes, immediately wash out with plenty of water
 - Seek medical attention if irritation persists
 - P331 - Do NOT induce vomiting.
 - P310 - Immediately call a POISON CENTER or doctor/physician.
-

SECTION 5 Fire-fighting measures

5.1 Extinguishing media

- P370+P378 - In case of fire: use foam, carbon dioxide or dry agent to extinguish.
- P370+P378 - In case of fire: Use

5.2 Special hazards arising from the substance or mixture

- Vapours may travel considerable distances to a source of ignition and flashback
- May give off noxious and toxic fumes in a fire
- Smoke from fires is irritating. Take precautions to protect personnel from exposure

5.3 Advice for firefighters

- Keep container(s) exposed to fire cool, by spraying with water
 - Wear Breathing Apparatus
-

SECTION 6 Accidental release measures

Vapours may ignite

6.1 Personal precautions, protective equipment and emergency procedures

- Spillage causes slippery surface
- Shut off source of leak if safe to do so
- Ensure adequate ventilation

6.2 Environmental Precautions

- Do not allow to enter public sewers and watercourses
- If contamination of drainage systems or water courses is unavoidable, immediately inform appropriate authorities
- P273 - Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

- Absorb spillage in inert material and shovel up
-

SECTION 6 Accidental release measures (....)

- Place in appropriate container
- Remove contaminated material to safe location for subsequent disposal
- To clean the floor and all objects contaminated by this material use soap and water

- P391 - Collect spillage.

6.4 Reference to other sections

- See Section 3,8 &13 for futher infomation
-

SECTION 7 Handling and storage

7.1 Precautions for safe handling

- Ensure adequate ventilation
- Proper chemicals handling procedures should be adopted
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ventilating/lighting/
- P242 - Use only non-sparking tools.
- P243 - Take precautionary measures against static discharge.
- P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 - Wash
- P270 - Do not eat, drink or smoke when using this product.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P314 - Get medical advice/attention if you feel unwell.
- P501 - Dispose of contents/container to

7.2 Conditions for safe storage, including any incompatibilities

- Keep in a cool, dry, well ventilated place
- P404 - Store in a closed container.
- Keep away from frost
- P233 - Keep container tightly closed.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ventilating/lighting/
- P403+P235 - Store in a well-ventilated place. Keep cool.
- P405 - Store locked up.

7.3 Specific end use(s)

- No hazardous reactions known if used for its intended purpose
-


SECTION 8 Exposure controls/personal protection

8.1 Control parameters

- xylene
WEL (long term) 220 mg/m³
WEL (short term) 441 mg/m³
- Hydrocarbons, C9-12, n-alkanes, isoalkanes, Cyclics, Aromatics (2-25%)
WEL (long term) 330 mg/m³

8.2 Exposure controls

SECTION 8 Exposure controls/personal protection (....)



- P280 - Wear protective gloves/protective clothing/eye protection/face protection.

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance: clear, colourless to yellow, Liquid
- Odour: Hydrocarbon odour
- Specific Gravity: 0.820
- Flashpoint: 34°C
- Solubility in water: Insoluble in water

9.2 Other information

- Volatile Organic Compound Content 100%

SECTION 10 Stability and reactivity

10.1 Reactivity

- This article is considered stable under normal conditions

10.2 Chemical stability

- This article is considered stable under normal conditions

10.3 Possibility of hazardous reactions

- No hazardous reactions known if used for its intended purpose

10.4 Conditions to avoid

- Keep away from frost

10.5 Incompatible materials

- No hazardous reactions known if used for its intended purpose

10.6 Hazardous Decomposition Products

- No hazardous decomposition products known

SECTION 11 Toxicological information

11.1 Information on toxicological effects

- Aspiration hazard
- Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

SECTION 12 Ecological information

12.1 Toxicity

- May cause acute effects in the aquatic environment

12.2 Persistence and degradability

SECTION 12 Ecological information (....)

- Biodegradable
- 12.3 Bioaccumulation Potential
- No information available
- 12.4 Mobility in soil
- Insoluble in water
- 12.5 Results of PBT and vPvB assessment
- Not a PBT according to REACH Annex XIII
- 12.6 Other Adverse Effects
- Toxic to sewage works organisms
-

SECTION 13 Disposal considerations

- 13.1 Waste treatment methods
- Do not empty into drains
 - Do not pierce or burn container, even after use
 - Do not reuse empty containers without commercial cleaning or reconditioning
 - P501 - Dispose of contents/container to
-

SECTION 14 Transport information



- 14.1 UN Number
- UN No.: 1139
- 14.2 Proper Shipping Name
- Proper Shipping Name: COATING SOLUTION
- 14.3 Transport hazard class(es)
- Hazard Class: 3
- 14.4 Packing group
- Packing Group: III
- 14.5 Environmental hazards
- Marine Pollutant
 - ENVIRONMENTALLY HAZARDOUS
- 14.6 Special precautions for user
- Transport Regulations apply as indicated in previous section
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC code
- Not applicable
-

SECTION 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
-

SECTION 15 Regulatory information (....)

- This Safety Data Sheet is provided in compliance with The Chemicals (Hazard Information and Packaging) Regulations
 - The CPL Regulations apply in the UK
-

SECTION 16 Other information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.